## NSN 5320-01-481-3511

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-481-3511 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.753 inches and 0.773 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Tip Diameter: Between 0.181 inches and 0.184 inches **Grip Length:** 0.443 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Product Name:** Hi-lok pin **Special Features:** Protruding shear head; a-286 high temperature alloy 1/16 in. Grip variation, 1/64 in. Oversize Material: Iron alloy 660 **Material Specification:** Ams5731 federal specification single material response or ams5737 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf **Specification Data:** 73197-hl140-6-7 professional/industrial association specification Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-481-3511

Pin-rivet - Page 2 of 2



D	:1:4.	-:-	-4:-	
Dem	HIT	arız	atıc	on:

No

Fiig:

A528u0