# NSN 5320-01-481-4833

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-481-4833

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.565 inches and 0.585 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.079 inches and 0.080 inches

#### Shank Diameter:

Between 0.188 inches and 0.189 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### Grip Length:

Between 0.245 inches and 0.255 inches

#### Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.190 inches

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

#### Material Specification:

Ams6415 assn standard 1st material response or mil-s-5625 military specification 2nd material response or mil-s-6049 military specification 3rd material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification all treatment responses

#### Thread Series Designator:

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

A528u0

# NSN 5320-01-481-4833

Pin-rivet - Page 2 of 2

### Mil-std (military Standard):

Mil-s-5625 spec.

