NSN 5320-01-481-5085

Pin-rivet - Page 1 of 1

Mil-std (military Standard):

Mil-s-8503 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-481-5085 **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Shank Diameter: Between 0.154 inches and 0.156 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.242 inches and 0.262 inches **Grip Length:** Between 1.376 inches and 1.438 inches Min. Tensile Strength (psi): 160000 pounds per square inch Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130 **Material Specification:** Mil-s-8503 military specification 1st material response or mil-s-6049 military specification 2nd material response or il-s-8503 military specification 10th material response or mil-s-5626 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-5000 military specification 6th material response or ams 6300 assn standard 7th material response or mil-s-6758 military specification 8th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Specification Data:** 80205-nas1054 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A528u0