

View Online at <https://aerobasegroup.com/nsn/5320-01-481-6112>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.223 inches and 1.243 inches

Head Style:

Err-090

Width Between Flats:

Between 0.158 inches and 0.162 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.756 inches and 0.760 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

End Application:

F18 e/f

Grip Length:

Between 0.683 inches and 0.693 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Criticality Code Justification:

Agav

Product Name:

Pin, riqvet, threaded-tension, 100 degree c sunk head, hex point drive

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0