
# NSN 5320-01-481-7667

Pin-rivet - Page 1 of 2





#### Thread Class:

3a

**Thread Direction:** 

Right-hand

#### Fastener Length:

Between 4.195 inches and 4.220 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

0.905 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 1.210 inches and 1.304 inches

#### Tip Diameter:

## 0.8709 inches

Lubrication:

Dry film

#### End Application:

Aircraft b-1b

#### Grip Length:

Between 3.365 inches and 3.390 inches

#### Thready Qty Per Inch (tpi):

16

#### Thread Size:

0.750 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Product Name:

Bolt-taper shank, shear, 100 degrees head, oversize

#### Material:

Steel comp xm-13

#### Material Specification:

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-481-7667

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

