NSN 5320-01-481-9386

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-481-9386 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.588 inches and 0.608 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Head Major Diameter:** Between 0.3213 inches and 0.3304 inches Lubrication: Dry film and cetyl alcohol **End Application:** F18 e/f **Grip Length:** Between 0.308 inches and 0.318 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1640 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin, rivet, flutted threads-tension, 100 degree c'sunk, hex point drive Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard 1st material response or ams 4967 assn standard 2nd material response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-481-9386

Pin-rivet - Page 2 of 2



Fiig:

A528u0