# NSN 5320-01-482-5742

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-482-5742

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

4.205 inches

## Head Style:

Flush countersunk

### Shank Diameter:

0.968 inches

Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 1.353 inches and 1.458 inches

#### **Tip Diameter:**

0.904 inches

# Lubrication:

Dry film and cetyl alcohol

# End Application:

Simulator, a-10

### Grip Length:

3.375 inches

## Thready Qty Per Inch (tpi):

14

### **Thread Size:**

0.875 inches

### **Countersink Angle:**

100.0 degrees

### Material:

Steel comp xm-13

### **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-482-5742

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

