

View Online at <https://aerobasegroup.com/nsn/5320-01-482-8954>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Red

**Fastener Length:**

0.637 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.2016 inches and 0.2026 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.312 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

3000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

8100 double pounds per square inch

**Special Features:**

Red identification on top of head

**Material:**

Steel comp 431

**Material Specification:**

Ams5628 assn standard single material response or mil-s-18732 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-18732 spec.