## NSN 5320-01-483-2031

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-483-2031 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.690 inches and 0.710 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **End Application:** Agusta helicopter **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 4010 double pounds per square inch Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-483-2031

Pin-rivet - Page 2 of 2



_						
ם ו	mil	11+2	riz	211	$\sim$	٦.
UC		IILa	114	аи	vi	и.

No

Fiig:

A528u0