NSN 5320-01-483-2132

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-483-2132 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.552 inches and 1.572 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3266 inches and 0.3276 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.933 inches and 0.943 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch Steel comp e4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-483-2132

Pin-rivet - Page 2 of 2



Fiig:

A528u0