NSN 5320-01-484-0786

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-484-0786 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.635 inches and 1.655 inches **Head Style:** Err-090 **Head Height:** Between 0.077 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style: Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Aircraft, thunderbolt ii, a-10 **Grip Length:** Between 1.245 inches and 1.255 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard 1st material response or ams5731 assn standard 2nd material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-484-0786

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0