

View Online at <https://aerobasegroup.com/nsn/5320-01-484-0791>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.822 inches and 1.842 inches

Head Style:

Err-090

Head Height:

Between 0.077 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2646 inches and 0.2651 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Aircraft, thunderbolt ii, a-10

Grip Length:

Between 1.432 inches and 1.442 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Material:

Iron alloy 660

Material Specification:

Ams5737 assn standard 1st material response or ams5731 assn standard 2nd material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0