
# NSN 5320-01-484-0943

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.000 inches and 2.020 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.150 inches and 0.180 inches

#### Width Between Flats:

Between 0.1895 inches and 0.1930 inches

#### Shank Diameter:

Between 0.4365 inches and 0.4370 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Dry film

End Application:

Aircraft, thunderbolt ii, a-10

# Grip Length:

Between 1.370 inches and 1.380 inches

## Thready Qty Per Inch (tpi):

20

## **Thread Size:**

0.073 inches

# Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp xm-13

## Material Specification:

Ams5629 assn standard single material response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-484-0943

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

