NSN 5320-01-484-3537

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-484-3537 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.125 inches and 2.145 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.4365 inches and 0.4370 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.8812 inches and 0.8884 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Aircraft, b-1b **Grip Length:** Between 1.495 inches and 1.505 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.073 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a

__

Unit Of Measure:

NSN 5320-01-484-3537

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0