

View Online at <https://aerobasegroup.com/nsn/5320-01-484-3539>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 3.652 inches and 3.677 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.8657 inches

**Shank Style:**

Pin-rivet, tapered, threaded

**Head Major Diameter:**

1.304 inches

**Tip Diameter:**

0.8110 inches

**Lubrication:**

Dry film and cetyl alcohol

**End Application:**

B-1b bomber

**Grip Length:**

Between 2.927 inches and 2.952 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Thread Size:**

0.7500 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Shear taper shank bolt

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0