

View Online at <https://aerobasegroup.com/nsn/5320-01-484-3556>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 3.370 inches and 3.395 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.7252 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

1.094 inches

**Tip Diameter:**

0.6731 inches

**Lubrication:**

Dry film and cetyl alcohol

**End Application:**

B-1b bomber

**Grip Length:**

Between 2.740 inches and 2.755 inches

**Thread Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Thread Size:**

0.6250 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Shear taper shank bolt

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0