NSN 5320-01-484-3556

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Flush countersunk

Between 3.370 inches and 3.395 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-484-3556

Shank Diameter:
0.7252 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
1.094 inches
Tip Diameter:
0.6731 inches
Lubrication:
Dry film and cetyl alcohol
End Application:
B-1b bomber
Grip Length:
Between 2.740 inches and 2.755 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.6250 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
100.0 degrees
Product Name:
Shear taper shank bolt
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

NSN 5320-01-484-3556

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0