
## NSN 5320-01-484-8487

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.385 inches and 1.405 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### **End Application:**

F-119-pw-100 for aft engine

#### Grip Length:

Between 0.995 inches and 1.005 inches

#### Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### **Product Name:**

Pin

## Material:

Nickel alloy 718

## Material Specification:

Ams 5662 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Per hi-shear specification 258 mfr ref single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-484-8487

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

