NSN 5320-01-485-5737

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-485-5737 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.052 inches and 1.072 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches Lubrication: Solid film and cetyl alcohol **End Application:** F18 de/f **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1640 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin-rivet, threded, shear, 100 degree c'sunk head, hex point drive Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate**

Surface Treatment Specification: Ams qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc

NSN 5320-01-485-5737

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0