NSN 5320-01-485-5796

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-485-5796

| Fastener Length: |
|---|
| 0.3675 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.061 inches and 0.065 inches |
| Shank Style: |
| Straight with tapered tip |
| Head Major Diameter: |
| 0.353 inches |
| Chamfer Length: |
| 0.047 inches |
| Tip Diameter: |
| 0.108 inches |
| End Application: |
| Door assembly, suu-80a/a pylon |
| Countersink Angle: |
| 100.0 degrees |
| Criticality Code Justification: |
| Agav |
| Special Features: |
| Rivet has dimple centered on head with a depth of 0.020 inches and a width of 0.030 inches |
| Material: |
| Aluminum alloy 2117 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 2, class 1, dichromate seal military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |