

View Online at <https://aerobasegroup.com/nsn/5320-01-485-6464>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.927 inches and 0.947 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.620 inches and 0.630 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Minimum Yield Strength:

3180 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

5380 double pounds per square inch

Special Features:

Dimensions to be met after finish; collar included

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Ams 6415 assn standard 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Chromate and chromium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.