## NSN 5320-01-487-0343

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-487-0343



## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 2.363 inches and 2.383 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.2207 inches and 0.2242 inches

#### Shank Diameter:

Between 0.4990 inches and 0.4995 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 1.0068 inches and 1.0139 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### **End Application:**

Aircraft, b-1b

### Grip Length:

Between 1.683 inches and 1.693 inches

#### Thready Qty Per Inch (tpi):

20

## Thread Size:

0.500 inches

## Shear Strength:

49100 double pounds per square inch

## Countersink Angle:

100.0 degrees

## Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

## Surface Treatment:

Passivate

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-487-0343

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

