

View Online at <https://aerobasegroup.com/nsn/5320-01-488-4246>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.628 inches and 0.648 inches

Head Style:

Err-090

Head Height:

Between 0.010 inches and 0.015 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2177 inches and 0.2182 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.3486 inches and 0.3536 inches

Head Minor Diameter:

Between 0.334 inches and 0.347 inches

Countersink Height:

Between 0.0547 inches and 0.0568 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 0.308 inches and 0.318 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-shear specification no 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0