

View Online at <https://aerobasegroup.com/nsn/5320-01-488-7472>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.690 inches and 0.710 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.115 inches and 0.135 inches

**Shank Diameter:**

Between 0.217 inches and 0.218 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.370 inches and 0.390 inches

**End Application:**

Helicopter ch53g fuselage

**Grip Length:**

Between 0.370 inches and 0.380 inches

**Thread Size:**

0.190 inches

**Shear Strength:**

7100 double pounds per square inch

**Material:**

Steel comp e4340 or steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-s-5000 military standard 1st material response or mil-s-5620 military standard 2nd material response or mil-s-6049 military standard 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.