# NSN 5320-01-489-1598

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-489-1598



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.9525 inches and 0.9725 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.104 inches and 0.119 inches

#### Shank Diameter:

Between 0.1810 inches and 0.1840 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.357 inches and 0.377 inches

### **End Application:**

Aircraft, stratoliftc-135

## Grip Length:

Between 0.5575 inches and 0.5675 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.250 inches

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Aluminumcoat/hi-shearspec294andcetylalcohollube/spec305 mfr ref 1st treatment response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-489-1598

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

