

View Online at <https://aerobasegroup.com/nsn/5320-01-489-1601>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.2025 inches and 1.2225 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.1810 inches and 0.1840 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**End Application:**

Aircraft, stratoliftc-135

**Grip Length:**

Between 0.8075 inches and 0.8175 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Aluminumcoat/hi-shearspec294andcetylalcohollube/spec305 mfr ref 1st treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0