NSN 5320-01-489-1603

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-489-1603 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.3275 inches and 1.3475 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.1810 inches and 0.1840 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **End Application:** Aircraft, stratoliftc-135 **Grip Length:** Between 0.9325 inches and 0.9425 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Aluminumcoat/hi-shearspec294andcetylalcohollube/spec305 mfr ref 1st treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-489-1603

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0