NSN 5320-01-489-1609

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-489-1609



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.0550 inches and 1.0750 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.1810 inches and 0.1840 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

End Application:

Aircraft, stratoliftc-135

Grip Length:

Between 0.3700 inches and 0.3800 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.500 inches

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Aluminumcoat/hi-shearspec294andcetylalcohollube/spec305 mfr ref 1st treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-489-1609

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

