NSN 5320-01-490-2142

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-490-2142

view Online at https://acrobasegroup.com/nsn/0020-01-400-2142
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.715 inches and 0.735 inches
Head Style:
Err-090
Head Height:
Between 0.059 inches and 0.069 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.387 inches and 0.412 inches
End Application:
F-22
Grip Length:
Between 0.370 inches and 0.380 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
4300 pounds per square inch
Thread Size:
0.2500 inches
Shear Strength:
9300 double pounds per square inch
Product Name:
Eddie-bolt 2 pin
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
Ams 2486 assn standard single treatment response
Thread Series Designator:
Inread Series Designator:

Unjf

NSN 5320-01-490-2142

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0