## NSN 5320-01-490-2257

Pin-rivet - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-490-2257

Thread Direction:
Right-hand
Fastener Length:
Between 1.122 inches and 1.142 inches
Head Style:
Err-090
Head Height:
Between 0.068 inches and 0.078 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.475 inches and 0.505 inches
End Application:
F-22
Grip Length:
0.6875 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 24
24
24 Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 8000 pounds per square inch
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size:
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength:
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name:
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material:
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material: Nickel alloy 718
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material: Nickel alloy 718 Material Specification:
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Min. Tensile Strength (psi): 8000 pounds per square inch Thread Size: 0.3125 inches Shear Strength: 19160 double pounds per square inch Product Name: Eddie-bolt 2 pin Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal standard single treatment response

## NSN 5320-01-490-2257

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0