NSN 5320-01-490-2289

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Between 0.525 inches and 0.545 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-490-2289

| Head Style: |
|--|
| Err-090 |
| Head Height: |
| Between 0.037 inches and 0.047 inches |
| Width Between Flats: |
| Between 0.0791 inches and 0.0806 inches |
| Shank Diameter: |
| Between 0.1630 inches and 0.1635 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.242 inches and 0.262 inches |
| End Application: |
| F-22; global hawk, rq-4a |
| Grip Length: |
| 0.2500 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 1940 pounds per square inch |
| Thread Size: |
| 0.1640 inches |
| Shear Strength: |
| 4010 double pounds per square inch |
| Product Name: |
| Eddie-bolt 2 pin |
| Special Features: |
| Material is 6a1-4v titanium |
| Material: |
| Titanium alloy |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Ams 2486 assn standard single treatment response |
| Thread Series Designator: |
| Unjc |
| |

NSN 5320-01-490-2289

Pin-rivet - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0