
# NSN 5320-01-490-2294

Pin-rivet - Page 1 of 2





**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.482 inches and 0.502 inches

### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### **End Application:**

F-22

## Grip Length:

0.1875 inches

# Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

2500 pounds per square inch

## Thread Size:

0.1900 inches

# Shear Strength:

5380 double pounds per square inch

## Product Name:

Eddie-bolt 2 pin

## **Special Features:**

Material is 6a1-4v titanium

# Material:

Titanium alloy

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Ams 2486 assn standard single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5320-01-490-2294

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

