# NSN 5320-01-490-3019

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-490-3019



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.778 inches and 0.798 inches

### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

# Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.381 inches and 0.412 inches

#### **End Application:**

F-22

# Grip Length:

0.4375 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

5100 pounds per square inch

### **Thread Size:**

0.2500 inches

# Shear Strength:

12260 double pounds per square inch

#### **Product Name:**

Eddie-bolt 2 pin

# Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-490-3019

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

