NSN 5320-01-490-3020

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-490-3020 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.372 inches and 1.392 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.602 inches **End Application:** F22 **Grip Length:** Between 0.932 inches and 0.942 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 14600 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees **Product Name:** Pin, shoulder, headless Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:**

N/a

Unjf

Shelf Life:

NSN 5320-01-490-3020

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0