NSN 5320-01-490-3095

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-490-3095 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.712 inches and 0.732 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Head Major Diameter:** 0.311 inches **End Application:** F22 **Grip Length:** Between 0.432 inches and 0.442 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1640 inches **Shear Strength:** 4010 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees **Product Name:** Pin, shoulder, headless Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-490-3095

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0