NSN 5320-01-490-3096

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-490-3096



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.108 inches and 1.128 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.350 inches

End Application:

F22

Grip Length:

Between 0.805 inches and 0.817 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

5380 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Product Name:

Pin, shoulder, headless

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Ams2486 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-490-3096

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

