
# NSN 5320-01-490-3104

Pin-rivet - Page 1 of 2





# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.732 inches and 0.752 inches

### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

#### 0.3813 inches

End Application:

F-22

#### Grip Length:

0.4375 inches

# Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

4350 pounds per square inch

#### **Thread Size:**

0.1900 inches

#### Shear Strength:

7060 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Product Name:**

Eddie-bolt 2 pin

#### Material:

Nickel alloy 718

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-01-490-3104

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

