## NSN 5320-01-490-3110

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-490-3110



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.482 inches and 0.502 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

0.112 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.324 inches

#### End Application:

F-22

#### Grip Length:

Between 0.183 inches and 0.193 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

5380 double pounds per square inch

## **Countersink Angle:**

Between 129.3 degrees and 130.3 degrees

## **Product Name:**

Pin, shoulder, headless

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

## Surface Treatment:

Phosphate

## Surface Treatment Specification:

Ams2486 assn standard single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-490-3110

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

