## NSN 5320-01-490-3111

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-490-3111 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.545 inches and 0.565 inches **Head Style:** Flush countersunk Width Between Flats: 0.112 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.293 inches **End Application:** F-22 **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 4010 double pounds per square inch **Countersink Angle:** Between 129.3 degrees and 130.3 degrees **Product Name:** Pin, shoulder, headless Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** 

N/a

Unjc

Shelf Life:

## NSN 5320-01-490-3111

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0