NSN 5320-01-490-3266

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-490-3266

| Fastener Length: |
|--|
| Between 0.965 inches and 0.985 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.080 inches and 0.090 inches |
| Width Between Flats: |
| Between 0.0947 inches and 0.0967 inches |
| Shank Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.415 inches and 0.440 inches |
| End Application: |
| F-22 |
| Grip Length: |
| 0.6250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 7750 pounds per square inch |
| Thread Size: |
| 0.2500 inches |
| Shear Strength: |
| 12260 double pounds per square inch |
| Product Name: |
| Eddie-bolt 2 pin |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal standard single treatment response |
| Thread Series Designator: |
| Unjf |

NSN 5320-01-490-3266

Pin-rivet - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0