NSN 5320-01-490-5165

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-490-5165

| Fastener Length: |
|--|
| 0.718 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.123 inches and 0.128 inches |
| Shank Style: |
| Self-plugging high clinch shank |
| Head Major Diameter: |
| 0.196 inches |
| Expansion Device: |
| Serrated stem-type w |
| End Application: |
| F-22 |
| Grip Length: |
| Between 0.376 inches and 0.437 inches |
| Min. Tensile Strength (psi): |
| 270 pounds per square inch |
| Shear Strength: |
| 185 single pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 305 stem |
| Material Specification: |
| Astm a-493 assn standard single material response stem |
| Surface Treatment: |
| Passivate stem |
| Surface Treatment Specification: |
| Qq-p-35 federal specification 1st treatment response stem and par 90 mfr ref 2nd treatment response stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| |