NSN 5320-01-490-5475

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-490-5475 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.060 inches and 1.080 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.6335 inches **End Application:** F-22 **Grip Length:** 0.6250 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 12300 pounds per square inch **Thread Size:** 0.3125 inches **Shear Strength:** 19160 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Eddie-bolt 2 pin **Special Features:** B suffix indicates cross-lock features in sc7000 Material: Nickel alloy 718 **Surface Treatment:**

Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

Thread Series Designator:

Unjf

Passivate

NSN 5320-01-490-5475

Pin-rivet - Page 2 of 2



She	lf	L	if	е	:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0