## NSN 5320-01-490-5492

Pin-rivet - Page 1 of 2





## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.748 inches and 0.768 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

0.6335 inches

## End Application:

F-22

## Grip Length:

0.3125 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

12300 pounds per square inch

#### **Thread Size:**

0.3125 inches

#### Shear Strength:

19160 double pounds per square inch

## **Countersink Angle:**

100.0 degrees

#### **Product Name:**

Eddie-bolt 2 pin

#### **Special Features:**

B suffix indicates cross-lock features in sc7000

#### Material:

Nickel alloy 718

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5320-01-490-5492

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

