

View Online at <https://aerobasegroup.com/nsn/5320-01-490-5492>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.748 inches and 0.768 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.6335 inches

**End Application:**

F-22

**Grip Length:**

0.3125 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

12300 pounds per square inch

**Thread Size:**

0.3125 inches

**Shear Strength:**

19160 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Eddie-bolt 2 pin

**Special Features:**

B suffix indicates cross-lock features in sc7000

**Material:**

Nickel alloy 718

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0