# NSN 5320-01-490-5890

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-490-5890



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.938 inches and 1.958 inches

### Head Style:

Err-090

#### Head Height:

Between 0.093 inches and 0.105 inches

#### Width Between Flats:

Between 0.4365 inches and 0.4370 inches

#### Shank Diameter:

Between 0.1895 inches and 0.1930 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.641 inches and 0.676 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## **End Application:**

F-22

### Grip Length:

1.3125 inches

## Thready Qty Per Inch (tpi):

20

### **Thread Size:**

0.437 inches

## Shear Strength:

37500 double pounds per square inch

#### **Product Name:**

Pin

# Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Per hi-shear specification 258 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-490-5890

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

