NSN 5320-01-490-5890

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-490-5890 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.938 inches and 1.958 inches **Head Style:** Err-090 **Head Height:** Between 0.093 inches and 0.105 inches Width Between Flats: Between 0.4365 inches and 0.4370 inches **Shank Diameter:** Between 0.1895 inches and 0.1930 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.641 inches and 0.676 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** F-22 **Grip Length:** 1.3125 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.437 inches **Shear Strength:** 37500 double pounds per square inch **Product Name:** Pin Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Per hi-shear specification 258 mfr ref single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-490-5890

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0