
# NSN 5320-01-490-6049

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.935 inches and 0.955 inches

## Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.475 inches and 0.505 inches

## **End Application:**

F-22

## Grip Length:

0.5000 inches

# Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

9200 pounds per square inch

## Thread Size:

0.3125 inches

## Shear Strength:

14600 double pounds per square inch

## **Product Name:**

Eddie-bolt 2 pin

## **Special Features:**

Material is 6a1-4v titanium

## Material:

Titanium alloy

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Ams 2486 assn standard single treatment response

# Thread Series Designator:

Unjf

# NSN 5320-01-490-6049

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

