## NSN 5320-01-490-7079

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

Head Style: Err-090

**Head Height:** 

**Thread Direction:** 

Fastener Length:

Between 0.778 inches and 0.798 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-490-7079

Between 0.080 inches and 0.090 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
End Application:
F-22
Grip Length:
0.4375 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
5820 pounds per square inch
Thread Size:
0.2500 inches
Shear Strength:
9300 double pounds per square inch
Product Name:
Eddie-bolt 2 pin
Special Features:
Material is 6a1-4v titanium
Material:
Titanium alloy
Surface Treatment:
Anodize
Surface Treatment Specification:
Ams 2486 assn standard single treatment response
Thread Series Designator:
Unjf

## NSN 5320-01-490-7079

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0