
# NSN 5320-01-490-7083

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.902 inches and 0.922 inches

## Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.415 inches and 0.440 inches

### **End Application:**

F-22

## Grip Length:

0.5625 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

5820 pounds per square inch

## Thread Size:

0.2500 inches

## Shear Strength:

9300 double pounds per square inch

## Product Name:

Eddie-bolt 2 pin

## **Special Features:**

Material is 6a1-4v titanium

## Material:

Titanium alloy

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Ams 2486 assn standard single treatment response

# Thread Series Designator:

Unjf

# NSN 5320-01-490-7083

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

