NSN 5320-01-490-7380

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Between 1.413 inches and 1.433 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-490-7380

| Err-090 |
|--|
| Head Height: |
| Between 0.130 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.1582 inches and 0.1617 inches |
| Shank Diameter: |
| Between 0.3740 inches and 0.3745 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.565 inches and 0.600 inches |
| End Application: |
| F-22 |
| Grip Length: |
| 0.9375 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 19100 pounds per square inch |
| Thread Size: |
| 0.3750 inches |
| Shear Strength: |
| 27600 double pounds per square inch |
| Product Name: |
| Eddie-bolt 2 pin |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal standard single treatment response |
| Thread Series Designator: |
| Unjf |
| |
| |

NSN 5320-01-490-7380

Pin-rivet - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0